




SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	Product Type
EN-DDL15/40	4000	1200	80	15	100	White	Triac Dimmable
EN-DDL15EM/40	4000	1100		15	100	White	Dimmable Emergency

Line Drawing

Polar Curve

Color



White

Product Features:

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver for easy installation and shallow ceiling voids
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44 rated
- Pre-wired with 500mm 2 core cable
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	Dimmable	Yes
IP Rating	IP44	Technology	LED
Luminaire Distribution	Accent	Lifetime L70 (hrs)	25000
Operating Temp	40°C	Overall Diameter (mm)	150
Lamp Base	None	Cutout Diameter (mm)	120
Weight (Kg)	0.254	Recess Depth (mm)	70
Positional Adjustment	Fixed	SDCM	6
LED Chip	2835	Positional Adjustment	Fixed

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.