





SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	Product Type
EN-DDL20/40	4000	1800	90	20	100	White	Triac Dimmable
EN-DDL20EM/40	4000	1500	75	20	100	White	Dimmable Emergency

Line Drawing

Polar Curve

Color



White

Product Features:

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver for easy installation and shallow ceiling voids
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44 rated
- Pre-wired with 500mm 2 core cable
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	Dimmable	Yes
Number of LEDs	60	IP Rating	IP44
Technology	LED	Luminaire Distribution	Accent
Lifetime L70 (hrs)	25000	Operating Temp	40°C
Overall Diameter (mm)	200	Lamp Base	None
Cutout Diameter (mm)	170	Weight (Kg)	0.370
Recess Depth (mm)	75	Positional Adjustment	Fixed
SDCM	6	LED Chip	2835
Positional Adjustment	Fixed		

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.