





SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	Product Type
EN-DDLH825/40	4000	2600	104	25	100	Matt White	Triac Dimmable
EN-DDLH825DA/40	4000	2600	104	25	100	Matt White	DALI Dimmable
EN-DDLH825V/40	4000	2600	104	25	100	Matt White	1-10V Dimmable

Line Drawing



Polar Curve



Color



Matt White

Product Features:

- Low cost energy saving compared to compact fluorescents
- Life not affected by frequent switching e.g. when used with occupancy controls
- Triac dimmable as standard
- Plug and play remote driver for easy installation
- DALI version available to order
- IP54 rated
- 1.5kV surge protection
- 5 year warranty

Product Specs:

Input Voltage	200~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	Dimmable	Yes
Number of LEDs	90	IP Rating	IP54
Colour Rendering (Ra)	80	Technology	LED
Luminaire Distribution	Accent	Lifetime L70 (hrs)	50000
IK Rating	IK06	Operating Temp	45°C
Optic Material	PMMA	Overall Diameter (mm)	228
Lamp Base	None	Cutout Diameter (mm)	210
Weight (Kg)	1.005	Recess Depth (mm)	70
Positional Adjustment	Baffle	SDCM	6
LED Chip	2835	Positional Adjustment	Baffle

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.