




Product Description: ELumi[™] 25W High Performance Non-Dimmable Downlight


The range of non-dimmable ELumi[™] commercial downlights deliver up to an impressive 115lm/W. Supplied with remote driver for ease of installation. Whether upgrading compact fluorescent fittings or new installations, this range meets the needs for countless applications.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DLH925/30	25	3000	2750	110	100	White	Non Dimmable
EN-DLH925/40	25	4000	2875	115	100	White	Non Dimmable

Line Drawing



Polar Curve



Color



White

Product Features:

- Low cost energy savings compared to compact fluorescents
- Plug and play remote driver for easy installation
- IP44 & IK03 rated
- L70 30,000hrs
- 5 Year Warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP44
Height (mm)	63	Lifetime L70 (hrs)	30000
Cutout Diameter (mm)	200	Overall Diameter (mm)	225
Operating Temp. (Min) °C	-20°C	Product Type	Downlights
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.